

4-68型NO. 2.8A、3.15A、3.55A性能参数表

机号	传动方式	转速 r/min	序号	流量m <sup>3</sup> /h	全压Pa	电动机	
						型号	功率
2.8	A	2900	1	1131	970	Y802-2	1.1
			2	1319	970		
			3	1508	961		
			4	1696	921		
			5	1885	853		
			6	2073	764		
			7	2262	657		
2.8	A	1450	1	565	245	Y801-4	0.55
			2	660	245		
			3	754	235		
			4	848	225		
			5	942	215		
			6	1037	186		
			7	1131	166		
3.15	A	2900	1	1825	1245	Y90S-2	1.5
			2	2093	1245		
			3	2362	1225		
			4	2630	1176		
			5	2899	1098		
			6	3167	980		
			7	3435	853		
3.15	A	1450	1	912	313	Y801-4	0.55
			2	1047	313		
			3	1181	304		
			4	1315	294		
			5	1449	274		
			6	1583	245		
			7	1718	215		
3.55	A	2900	1	2708	1608	Y100L-2	3
			2	3092	1608		
			3	3477	1569		
			4	3861	1510		
			5	4245	1402		
			6	4629	1265		
			7	5013	1108		
3.55	A	1450	1	1354	402	Y801-4	0.55
			2	1546	402		
			3	1738	392		
			4	1930	372		
			5	2122	353		
			6	2315	313		
			7	2507	274		

4-68型NO. 4A、4.5A、5A性能参数表

机号	传动方式	转速r/min	序号	流量m <sup>3</sup> /h	全压Pa	电动机	
						型号	功率
4	A	2900	1	3984	2069	Y112M-2	4
			2	4534	2059		
			3	5083	2010		
			4	5633	1931		
			5	6182	1794		
			6	6732	1627		
			7	7281	1431		
4	A	1450	1	1992	519	Y802-4	0.75
			2	2267	509		
			3	2542	500		
			4	2816	480		
			5	3091	451		
			6	3366	402		
			7	3641	353		
4.5	A	2900	1	5790	2657	Y132S2-2	7.5
			2	6573	2628		
			3	7355	2569		
			4	8137	2461		
			5	8920	2294		
			6	9702	2069		
			7	10485	1833		
4.5	A	1450	1	2895	666	Y90S-2	1.1
			2	3286	657		
			3	3678	637		
			4	4069	617		
			5	4460	568		
			6	4851	519		
			7	5242	460		
5	A	2900	1	8050	3314	Y160M2-2	15
			2	9123	3265		
			3	10197	3187		
			4	11270	3049		
			5	12343	2844		
			6	13416	2589		
			7	14490	2304		
5	A	1450	1	4025	823	Y100L1-4	2.2
			2	4562	813		
			3	5098	794		
			4	5635	764		
			5	6172	715		
			6	6708	647		
			7	7245	578		

4-68型NO. 6.3D、8D性能参数表

机号	传动方式	转速 r/min	序号	流量m <sup>3</sup> /h	全压Pa	电动机	
						型号	功率
6.3	D	1450	1	8320	1323	Y132S-4	5.5
			2	9393	1304		
			3	10467	1274		
			4	11540	1216		
			5	12614	1137		
			6	13678	1039		
			7	14761	921		
6.3	D	960	1	5508	578	Y112M-6	2.2
			2	6219	568		
			3	6930	558		
			4	7641	529		
			5	8351	500		
			6	9062	451		
			7	9773	402		
8	D	1450	1	17585	2157	Y180M-4	18.5
			2	19783	2118		
			3	21982	2059		
			4	24179	1971		
			5	26378	1842		
			6	28576	1676		
			7	30774	1500		
8	D	960	1	11643	941	Y132M2-6	5.5
			2	13098	931		
			3	14553	902		
			4	16009	863		
			5	17464	804		
			6	18919	735		
			7	20375	657		
8	D	730	1	8853	549	Y132M-8	3
			2	9960	539		
			3	11067	519		
			4	12173	500		
			5	13280	470		
			6	14387	421		
			7	15403	382		

4-68型NO. 10D、12.5D性能参数表

机号	传动方式	转速	序号	流量	全压	电动机	
		r/min		m <sup>3</sup> /h	Pa	型号	功率
10	D	1450	1	35420	3442	Y250M-4	55
			2	39713	3363		
			3	44006	3265		
			4	48299	3108		
			5	52593	2922		
			6	56886	2678		
			7	61179	2422		
10	D	960	1	23450	1510	Y200L1-6	18.5
			2	26293	1480		
			3	29135	1431		
			4	31978	1363		
			5	34820	1274		
			6	37662	1176		
			7	40505	1059		
10	D	730	1	17832	872	Y160L-8	7.5
			2	19993	853		
			3	22155	823		
			4	24316	784		
			5	26478	735		
			6	28639	676		
			7	30801	617		
12.5	D	960	1	45800	2353	Y280M-6	55
			2	51353	2304		
			3	56904	2235		
			4	62456	2128		
			5	68008	2000		
			6	73559	1833		
			7	79111	1657		
12.5	D	730	1	34828	1363	Y225M-8	22
			2	39050	1333		
			3	43271	1294		
			4	47492	1235		
			5	51714	1157		
			6	55936	1059		
			7	60157	961		

4-68型NO. 6. 3C性能参数表

机号	传动方式	转速	序号	流量	全压	电动机	
		r/min		m <sup>3</sup> /h	Pa		
6.3	C	2240	1	12852	3159	Y180M-2	22
			2	14511	3108		
			3	16169	3030		
			4	17828	2893		
			5	19486	2706		
			6	21144	2490		
			7	22803	2196		
6.3	C	2000	1	11476	2510	Y160M2-2	15
			2	12956	2481		
			3	14437	2412		
			4	15917	2304		
			5	17398	2157		
			6	18879	1971		
			7	20359	1755		
6.3	C	1800	1	10328	2040	Y160M1-2	11
			2	11660	2010		
			3	12993	1951		
			4	14325	1863		
			5	15658	1745		
			6	16991	1588		
			7	18324	1422		
6.3	C	1600	1	9180	1608	Y132S2-2	7.5
			2	10365	1588		
			3	11550	1549		
			4	12734	1471		
			5	13918	1382		
			6	1510, 3	1255		
			7	16287	1117		
6.3	C	1400	1	8032	1235	Y132S-4	5.5
			2	9069	1216		
			3	10105	1186		
			4	11142	1127		
			5	12178	1059		
			6	13215	961		
			7	14251	863		
6.3	C	1250	1	7172	980	Y112M-4	4
			2	8098	970		
			3	9024	941		
			4	9949	902		
			5	10874	843		
			6	11799	764		
			7	12724	686		

6.3	C	1120	1	6426	784	Y100L2-4	3
			2	7255	774		
			3	8085	755		
			4	8913	725		
			5	9743	676		
			6	10572	617		
			7	11401	549		
6.3	C	1000	1	5737	627	Y100L1-4	2.2
			2	6478	617		
			3	7218	607		
			4	7958	578		
			5	8699	539		
			6	9439	490		
			7	10179	441		
6.3	C	900	1	5164	509	Y90L-4	1.5
			2	5830	500		
			3	6497	490		
			4	7163	470		
			5	7829	441		
			6	8496	402		
			7	9162	353		
6.3	C	800	1	4590	402	Y90S-4	1.1
			2	5182	392		
			3	5775	382		
			4	6367	372		
			5	6959	343		
			6	7552	313		
			7	8144	284		

4-68型NO. 8C性能参数表

机号	传动方式	转速 r/min	序号	流量m <sup>3</sup> /h	全压Pa	电动机	
						型号	功率KW
8	C	1800	1	21830	3314	Y200L2-2	37
			2	24559	3265		
			3	27288	3177		
			4	30016	3030		
			5	32745	2834		
			6	35474	2589		
			7	38202	2314		
8	C	1600	1	19404	2618	Y200L1-2	30
			2	21830	2579		
			, 3	24256	2510		
			4	26681	2392		
			5	29108	2235		
			6	31532	2049		
			7	33958	1833		
8	C	1400	1	16979	2009	Y180M-4	18.5
			2	19101	1970		
			3	21224	1921		
			4	23346	1833		
			5	25468	1715		
			6	27591	1568		
			7	29713	1401		
8	C	1250	1	15159	1597	Y160L-4	15
			2	17054	1568		
			3	18949	1529		
			4	20844	1460		
			5	22739	1362		
			6	24634	1245		
			7	26528	1117		
8	C	1120	1	13583	1284	Y160M-4	11
			2	15281	1264		
			3	16979	1225		
			4	18677	1176		
			5	20375	1098		
			6	22073	1000		
			7	23770	892		
8	C	1000	1	12128	1019	Y132M-4	7.5
			2	13644	1009		
			3	15160	980		
			4	16676	931		
			5	18192	872		
			6	19708	794		
			7	21224	715		

8	C	900	1	10915	833	Y132S-4	5.5
			2	12279	813		
			3	13644	794		
			4	15008	755		
			5	16373	706		
			6	17738	647		
			7	19101	578		
8	C	800	1	9702	657	Y112M-4	4
			2	10915	637		
			3	12128	627		
			4	13340	598		
			5	14554	558		
			6	15767	509		
			7	16979	460		
8	C	710	1	8611	519	Y100L2-4	3
			2	9687	509		
			3	10763	490		
			4	11840	470		
			5	12916	441		
			6	13992	402		
			7	15069	362		
8	C	630	1	7641	402	Y100L1-4	2.2
			2	8596	402		
			3	9551	392		
			4	10506	372		
			5	11461	343		
			6	12416	313		
			7	13371	284		



4-68型NO. 10C性能参数表

机号	传动方式	转速 r/min	序号	流量m <sup>3</sup> /h	全压Pa	电动机	
						型号	功率KW
10	C	1250	1	30543	2558	Y225S-4	37
			2	34235	2499		
			3	37936	2421		
			4	41637	2313		
			5	45338	2166		
			6	49040	1988		
			7	52740	1793		
10	C	1120	1	27358	2048	Y200L-4	30
			2	30674	2009		
			3	33990	1940		
			4	37307	1852		
			5	40623	1735		
			6	43939	1567		
			7	47256	1441		
10	C	1000	1	24427	1637	Y180L-4	22
			2	27388	1597		
			3	30349	1548		
			4	33310	1480		
			5	36270	1382		
			6	39233	1274		
			7	42192	1147		
10	C	900	1	21984	1323	Y160L-4	15
			2	24649	1294		
			3	27314	1254		
			4	29978	1196		
			5	32644	1127		
			6	35308	1029		
			7	37974	931		
10	C	800	1	19541	1049	Y160M-4	11
			2	21910	1019		
			3	24279	990		
			4	26648	941		
			5	29017	882		
			6	31385	813		
			7	33754	735		
10	C	710	1	17343	823	Y132M-4	7.5
			2	19446	804		
			3	21548	784		
			4	23650	745		
			5	25752	696		
			6	27854	647		
			7	29956	578		

10	C	630	1	15389	647	Y132S-4	5.5
			2	17254	637		
			3	19119	617		
			4	20985	588		
			5	22850	549		
			6	24716	509		
			7	26581	460		
10	C	560	1	13679	509	Y112M-4	4
			2	15337	500		
			3	16995	490		
			4	18654	460		
			5	20311	431		
			6	21969	402		
			7	23627	302		
10	C	500	1	12214	411	Y100M-4	3
			2	13694	402		
			3	15175	392		
			4	16655	372		
			5	18135	343		
			6	19616	313		
			7	21096	284		

4-68型NO. 12. 5C性能参数表

机号	传动方式	转速 r/min	序号	流量	全压	电动机	
				m <sup>3</sup> /h	Pa	型号	功率
12.5	C	1120	1	53434	3206	Y280S-4	75
			2	29912	3138		
			3	66388	3040		
			4	72865	2902		
			5	79342	2716		
			6	85819	2500		
			7	92296	2255	Y280M-4	90
12.5	C	1000	1	47710	2559	Y250M-4	55
			2	53492	2500		
			3	29276	2422		
			4	65058	2314		
			5	70841	2167		
			6	76624	1990		
			7	82407	1794	Y280S-4	75
12.5	C	900	1	42938	2069	Y280S-6	45
			2	48144	2030		
			3	53348	1961		
			4	58552	1873		
			5	63758	1755		
			6	68962	1618		
			7	74166	1451		
12.5	C	800	1	38168	1637	Y225M-6	30
			2	42794	1598		
			3	47424	1549		
			4	52046	1480		
			5	56673	1382		
			6	61300	1274		
			7	65926	1147		
12.5	C	710	1	33874	1284	Y200L2-6	22
			2	37980	1265		
			3	42086	1225		
			4	46191	1167		
			5	50297	1088		
			6	54403	1000		
			7	58509	902		
12.5	C	630	1	30057	1010	Y180L-6	15
			2	33700	990		
			3	37344	961		
			4	40987	912		
			5	44630	863		
			6	48273	794		
			7	51917	706		

12.5	C	560	1	26717	804	Y160L-6,	11
			2	29956	784		
			3	33194	755		
			4	36433	725		
			5	39671	676		
			6	42910	627		
			7	46148	558		
12.5	C	500	1	23855	637	Y160M-6	7.5
			2	26746	627		
			3	29638	608		
			4	32529	578		
			5	35421	539		
			6	38312	500		
			7	41204	451		
12.5	C	450	1	21469	519	Y132M2-6	5.5
			2	24071	509		
			3	26674	490		
			4	29276	470		
			5	31879	441		
			6	34481	402		
			7	37083	362		
12.5	C	400	1	19084	411	Y132M1-6	4
			2	21397	402		
			3	23710	392		
			4	26023	372		
			5	28337	343		
			6	30650	313		
			7	32963	284		